



orimat.

POLYURETHANE PRODUCTS

Basic information about the system
mathermic /M.A.T. Sp.z o.o.

page 1/1

The most important information about the system mathermic®

We offer 10-row modules mathermic® with 5 kinds of clinker tiles:

1. 250x65 mm
2. 240x71 mm
3. 215x65 mm
4. 240X65 mm
5. 290x52 mm

At the moment we cooperate with four clinker tiles producers: polish Klinkier Przysucha and CRH Klinkier, german Feldhaus and belgian Nelissen and Vandersanden

Module mathermic® can have seven different thicknesses: 40 mm, 50 mm and 60mm.

The mathermic® module is consisted of:

- the module with 45 clinker tiles inserted in the polymerization process
- 5 tiles needed to be pasted on the special places on both vertical connecting spaces of modules
- 12 EJOT tube washers TE embedded in the module defining a mounting space
- layer of a polyurethane thermal insulation
- 5 mm of sand,

The assembly materials:

- Ejot connectors - SDF.S plus 8uB (an anchor consisting of a plastic sleeve and accompanying specific metal screw) ,
- mortar grouting quick-mix Lobatherm P RFS (in chosen color)
- an adhesive mortar quick-mix Lobatherm P RKS
- mounting foam Soudal

Indicative value of assembly materials per 1 m2 of facade

Ejot connectors	9 pcs.
mortar grouting quick-mix Lobatherm P RFS	4,5 kg
an adhesive mortar quick-mix Lobatherm P RKS	3 kg
mounting foam Soudal	0,2 of pack